

The M3 GYS AUTO is a Synergic single phase MIG-MAG with 3 torch connectors recommended for welding steel, stainless steel, aluminium and for MIG Brazing of high-tensile strength steels with CuSi3 and CuAl8 wires (ideal for car body repairs).

Synergic Mode

• The machine determines the optimum wire speed by selecting :

- the type of wire
- the wire diameter
- the welding current



Spool gun

The M3 GYS AUTO is delivered with a Spool Gun torch. This motorised torch is suitable for aluminium, stainless steel, copper and steel ø100mm wire reels.

- Ideal for soft wire such as AlSi5 or AlSi12 (recommended for car body repairs)
- Ease of use : adjust the wire speed directly on the Spool Gun torch.
- The machine is delivered with a balancing system to support the Spool Gun torch.



4 Drive rolls motor

Suitable for ø200mm and ø300mm wire reels (15kg max).


Saving welding parameters

Memory save feature for each torch and activation of the 'last used' welding parameters (wire diameter, wire type and mode).

Accessories

- Delivered with:
- 2 steel torch 150A - 3m
 - 1 Spool Gun
 - 1 earth clamp 200A - 3m
 - 1 Balancing system (regulator not included)

+ PRODUIT



2 torches, 2 integrated wire feeder + 1 Spool Gun - The M3 GYS AUTO is a multifunctional and flexible machine designed to weld 3 different type of wire or diameter at the same time. It's saving time by avoiding disassembling the torch and changing the wire reel for another job.

Capable of welding:

- Soft wires: as AlSi and CuAl necessary for welding HLE/THLE metal sheets
- Aluminium wires
- Steel wires

CE - EN 60974-1

| 50/60hz | AM | min▷max | ø mm | 100 | 200 | 300 | équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica | EN60974-1 (40°C) | cm/kg | Protected & compatible POWER GENERATOR (+/- 15%) | Spool Gun | |
|----------|-----|---------|---------|-----|-----|-----|---|----------------------|-------------------------|--|-----------|----------|
| 230V | 16A | 15▷160A | 0.6-1.0 | | ✓ | ✓ | | I _A (60%) | X% (I ₂ max) | 60x90x90 67 | 4,5 kVA | Included |
| 208/240V | | | | | | | | 90A | 140A 15% | | | |